



Effects of Vibrations on Concrete Floor and Composite Concrete Floor

By Mohammad Nurul Hoque

LAP Lambert Academic Publishing Jan 2012, 2012. Taschenbuch. Book Condition: Neu. 220x150x7 mm. This item is printed on demand - Print on Demand Neuware - The generation of the impact sound by the act of the human walk involves two factors, the character of the footfall and the shape of the induced floor vibration. High levels of vibrations can occur in floor systems due to excitation from human activities such as walking and aerobics. In building floors, excessive vibrations are generally not a safety concern for building floor system but a cause of annoyance and discomfort. The footfall noise is created by the impact excitation where the character of the footfall depends on the foot-ware: the heels and the frequencies of the footfall. The shape of the floor deflection depends rather on the geometrical walking pattern and construction of the floor structure. Two types of floors are used for this experiment (1) Profiled Steel Sheet Concrete Floor (PCF) and Composite Concrete Floor (CCF). Since the excitation is assumed to be deterministic, differences between the excitation masses, acting forces and damping are determine from Bruel & Kjaer vibration analyzer machine. The goal of this investigation is to determine the differences of...



READ ONLINE
[3.97 MB]

Reviews

It becomes an amazing pdf which i actually have at any time read through. This can be for all those who statte there had not been a worthy of reading through. You wont sense monotony at anytime of your own time (that's what catalogues are for relating to should you check with me).

-- **Claud Kris**

If you need to adding benefit, a must buy book. It is writter in easy words and phrases and not difficult to understand. Your daily life span is going to be transform when you complete reading this article publication.

-- **Ricky Leannon**